

Exact™ 3027A

Ethylene-based Plastomer Resin

Product Description

Exact™ 3027A resin is an ethylene-based butene plastomer produced using ExxonMobil's EXXPOL® Catalyst Technology. It is designed for use in both monolayer and multilayer cast film applications requiring excellent toughness and heat sealing performance. Typical applications include seal layers for meat, poultry and cheese packaging, lamination films, heavy duty bags and cereal box liner packaging. TnPP is not intentionally added to Exact™ 3027A resin.

General			
Availability ¹	 Latin America 	 North America 	
Additive	 Antiblock: No 	Slip: No	 Thermal Stabilizer: Yes
Applications	 Cast Film 	 Heavy Duty Bags 	 Lamination Film
Form(s)	 Pellets 		
Revision Date	1 0/23/2019		

Resin Properties	Typical Value	(English)	Typical Value	(SI)	Test Based On
Density	0.900	g/cm³	0.900	g/cm³	ASTM D1505
Melt Index (190°C/2.16 kg)	3.5	g/10 min	3.5	g/10 min	ASTM D1238

Legal Statement

Contact your ExxonMobil Chemical Customer Service Representative for potential food contact application compliance (e.g. FDA, EU, HPFB).

Tris(nonylphenol)phosphite (TNPP) CAS# 26523-78-4 is not intentionally used by ExxonMobil in this product. Although this product is not routinely tested for its presence, based on product composition knowledge this substance is not expected to be present. However, the fact that this substance is not intentionally used by ExxonMobil in this product does not exclude that trace levels of this substance may be present as a result of the specific characteristics of the raw materials and/or of the manufacturing process.

This product is not intended for use in medical applications and should not be used in any such applications.

Notes

Typical properties: these are not to be construed as specifications.

¹ Product may not be available in one or more countries in the identified Availability regions. Please contact your Sales Representative for complete Country Availability.

For additional technical, sales and order assistance: www.exxonmobilchemical.com/ContactUs

©2022 ExxonMobil. ExxonMobil, the ExxonMobil logo, the interlocking "X" device and other product or service names used herein are trademarks of ExxonMobil, unless indicated otherwise. This document may not be distributed, displayed, copied or altered without ExxonMobil's prior written authorization. To the extent ExxonMobil authorizes distributing, displaying and/or copying of this document, the user may do so only if the document is unaltered and complete, including all of its headers, footers, disclaimers and other information. You may not copy this document to or reproduce it in whole or in part on a website. ExxonMobil does not guarantee the typical (or other) values. Any data included herein is based upon analysis of representative samples and not the actual product shipped. The information in this document relates only to the named product or materials when not in combination with any other product or materials. We based the information on data believed to be reliable on the date compiled, but we do not represent, warrant, or otherwise guarantee, expressly or impliedly, the merchantability, fitness for a particular purpose, freedom from patent infringement, suitability, accuracy, reliability, or completeness of this information or the products, materials or processes described. The user is solely responsible for all determinations regarding any use of material or product and any process in its territories of interest. We expressly disclaim liability for any loss, damage or injury directly or indirectly suffered or incurred as a result of or related to anyone using or relying on any of the information in this document. This document is not an endorsement of any non-ExxonMobil product or process, and we expressly disclaim any contrary implication. The terms "we," "our," "ExxonMobil Product Solutions" and "ExxonMobil" are each used for convenience, and may include any one or more of ExxonMobil Product Solutions Company, Exxon Mobil Corporation, or any affiliate either directly or indirectly stewarded.

exxonmobilchemical.com

Effective Date: 10/23/2019 ExxonMobil Page: 1 of 1